

C&M POST GROUT TUBE IN 20' LENGTHS

An economical method of increasing anchor bond value

Drilling contractors across the U.S. are finding that it is most economical to order pre-fabricated post grout tubing and riser pipe, thus reducing field labor costs. C&M's post grout tubing has proven its reliability on countless projects throughout the U.S.



Short lengths available for field assembly



.5" Schedule 40 Post Grout Tube x 20'



.25"x.25" notched grout outlet

SIZE	I.D.	MATERIAL	LENGTH
.50" 4 Outlets on 5' Centers	.622	Sch.40 PVC 600 PSI	20'
.50" 5 Outlets on 4' Centers	.622	Sch.40 PVC 600 PSI	20'
.75" 4 Outlets on 5' Centers	.824	Sch.40 PVC 480 PSI	20'
.75" 5 Outlets on 4' Centers	.824	Sch.40 PVC 480 PSI	20'
.75" 4 Outlets on 5' Centers	.742	Sch.80 PVC 690 PSI	20'
.75" 5 Outlets on 4' Centers	.742	Sch.80 PVC 690 PSI	20'
1.00" 4 Outlets on 5' Centers	1.049	Sch.40 PVC 450 PSI	20'
1.00" 5 Outlets on 4' Centers	1.049	Sch.40 PVC 450 PSI	20'
1.00" 4 Outlets on 5' Centers	0.957	Sch.80 PVC 630 PSI	20'
1.00" 5 Outlets on 4' Centers	0.957	Sch.80 PVC 630 PSI	20'

May also be ordered per anchor length & bond requirements.
 Schedule 40 Material, standard belled end.
 Schedule 80 Material, standard straight end.

ADVANTAGES

- Only quality type 1120 PVC pipe used.
- Grout outlets precision cut to .250" x .250".
- Outlet conformity improves pressure control and reduces pipe breakage.
- Gum rubber sleeves are highest quality available, 60 Duro, .125" wall x 4" length, permanently centered over grout outlet.
- All fittings attached with primer and cement to manufacturer's specifications.
- Factory belled ends for quick connections.
- PVC pipe meets or exceeds ASTM D1785.
- Same day shipping.

Plain PVC pipe, caps, couplers, adapters, primer/cement, etc. also available

C&M Manufacturing Co.

9640-B Mission Gorge Road #165, Santee, CA 92071 • 800-458-6191 • 619-449-7200 • 619-449--0018 FAX
 www.centralizers.com • e-mail: curt@centralizers.com