

PVC SPECIALTY TUBING & HDPE GROUT TUBING (Tube-a-Manchette)



20,000 LF - Dana Point, CA project

PVC SPECIALTY TUBING (Tube-a-Manchette)

PVC tubes have four drilled holes offset at 90° and spaced on 15" centers. The holes are covered with a gum-rubber sleeve and taped at each end. Available in 1", 1.5" or 2" Schedule 40 in specified lengths through 20'. Belled (spicket) ends available on 20' lengths. Schedule 40 couplers and caps available for all diameters. Custom thin wall fittings (do not exceed rubber o.d.) available for small diameter holes. Other valve spacing available.

12" lengths
0.80 x 4" sleeves



STANDARD PVC PIPE & FITTINGS

Available for bond breaker sheathing, grout tube, post grout tube risers and drainage systems. Custom pipe slotting available for drainage fabric requirements.

All standard Class 200, Schedule 40 & Schedule 80 PVC pipe available in 20' lengths. Class 200 & Sch. 40 w/ belled ends. Schedule 80 w/ plain ends.

All standard PVC fittings, valves and drain grates available.

PVC primers & cements.

HIGH DENSITY PE GROUT TUBING

For industry-wide grouting requirements. 6-stock sizes available, from 3/8" to 2" diameter. Standard 100' rolls; custom lengths available.

HDPE Trimmie & Primary Grout Tube



O.D.	I.D.	WALL	MAX PSI
3/8"	1/4"	.0625	272 PSI @ 70°
1/2"	3/8"	.0625	194 PSI @ 70°
3/4"	5/8"	.0625	123 PSI @ 70°
1"	7/8"	.0625	90 PSI @ 70°
1"	3/4"	.125	195 PSI @ 70°

2" HDPE trimmie pipe .216 wall thickness
Fits Victaulic fittings. Standard 500' rolls;
Custom lengths available.

C&M Manufacturing Co.

9640-B Mission Gorge Road #165, Santee, CA 92071 • 800-458-6191 • 619-449-7200 • 619-449-0018 FAX
www.centralizers.com • e-mail: curt@centralizers.com